

EUROPEAN FEDERATION OF RADIO OPERATED MODEL AUTOMOBILES

UPDATE New
Approved Batteries 2006
life cycle

All previously approved batteries keep their approval for their natural

Picture as

Manufacturer	TYPE / Range	illustration only	EFRA Specification,	Approval date
Intellect	SC-3600		New specifications 2006 Diam 23,0 +0/-1,0mm H: 43,0 +0/ -0,5mm W: 65 +/- 2g	31.12.2005
Intellect	SC-3800		High-drain type Diam 23,0 +0/-1,0mm H: 43,0 +0/ -0,5mm W: 66 +/- 2g	31.12.2005
Intellect	SC-4200		High-drain type Diam 23,0 +0/-1,0mm H: 43,0 +0/ -0,5mm W: 66 +/- 2g	31.12.2005
Intellect	YOKOMO SC-3800		X3800IB - Zap2 Diam 23,0 +0/-1,0mm H: 43,0 +0/ -0,5mm W: 64 +/- 2g	31.12.2005
Intellect	YOKOMO SC-4200		X4200IB - Zap2 Diam 23,0 +0/-1,0mm H: 43,0 +0/ -0,5mm W: 66 +/- 2g	31.12.2005
VTEC	SC-3700UP		Ultra performance Diam 23,0 +0/-1,0mm H: 43,0 +0/ -0,5mm W: 64 +/- 2g	31.12.2005
VTEC	SC-3800UP		3800 Fat Boy Diam 23,0 +0/-1,0mm H: 43,4 +0/ -0,5mm W: 65 +/- 2g	31.12.2005
VTEC	SC-4200UP		4200 Big Mama Diam 23,0 +0/-1,0mm H: 43,0 +0/ -0,5mm W: 66 +/- 2g	31.12.2005
Yungton	SC-4000		Batt 4000 Diam 23,0 +0/-1,0mm H: 43,0 +0/ -0,5mm W: 66 +/- 2g	31.12.2005
Yungton	SC-4100		TORNADO Diam 23,0 +0/-1,0mm H: 43,0 +0/ -0,5mm W: 66,5 +/- 2g	31.12.2005
? Made in China	INFINITE POWER IP3800SC		IP3800SC Diam 23,0 +0/-1,0mm H: 43,3 +0/ -0,5mm W: 68,5 +/- 2g	31.12.2005
GP	GP 4300SCHR		Gold Peak 4300 Diam 23,0 +0/-1,0mm H: 43,3 +0/ -0,5mm W: 66 +/- 2g	31.12.2005
Note:2007: ONLY "raw" batteries (not yet treated) may be submitted and specification 23/43mm will be strictly adhered to				
EAST POWER	EP4200SC		East Power NI-MH rechargeable 4200 Diam 23,0 +0/-1,0mm H: 43 +0/ -0,5mm W:70 +/- 2g	Range Efra sample specs: 22,8- 22,9 & 42,8 -42,9 70,4 -72g 30.09.2006

