



APPROVED 2S. 'STICK' Lithium (LiFe) BATTERY LIST. 2017 v1.

List shows years :- All to 2017.

Only Batteries detailed below are approved for EFRA Sanctioned Events.

EUROPEAN FEDERATION RADIO CONTROLLED AUTOMOBILES.

BATTERIES ON THIS HOMOLOGATION LIST HAVE BEEN CERTIFIED FOR COMPLIANCE WITH UN38.3, TESTS T1-T8.

Lithium based (LiPo) batteries detailed below, are approved for various EFRA Electric Classes. Section Rules will detail the type applicable. Availability dates for new EFRA compliant Packs are not known at the date of publishing this list. Manufacturers have confirmed March 2017 latest.

EFRA rules do not limit battery power output, but energy capacity has to comply with Airline Requirements, based on Manufacturers data below.






Batteries approved from 2011 onwards must comply with the weight range specified. Batteries factory sealed (glue, weld etc.).

Battery packs must be able to be disconnected within the Car quickly without the use of tools. Direct soldering is not allowed.

Manufacturers advise that charge rate be restricted to 1C for optimum lifespan, but should not be more than stated below (for 2017 on).

Batteries MUST be charged using a 2S LiFe compatible charger. LiPo 'Sack' must be used when charging or discharging prior to race.

It is strictly NOT ALLOWED, to charge 2S LiFe Batteries to give an output voltage exceeding 7.40v.

Submitted by:	Label Details Part #	Illustration only	Manufacturer Supplied Data.	EFRA measured Specification,	Approval Date
BATTERIES BELOW THIS LEVEL WERE APPROVED BY EFRA FOR 2013 AND ARE ALLOWED AT ALL 2017 EVENTS.					
Graupner	GM V-MAXX. # 99080		GM LiFe 2S 6.6v. 33.0 Wh. 40C Wt. 278/302 g.	Complies with EFRA. specified dimensions. Wt. 290.3 g.	02.01.13
BATTERIES BELOW THIS LEVEL WERE APPROVED BY EFRA FOR 2010 AND ARE ALLOWED AT ALL 2017 EVENTS.					
ORION	ORION Carbon. # ORI15012		Orion LiFe 2S 6.6v. 3800. 60C	Length: 138.51 mm. Width: 46.49 mm. High: 24.75 mm. Wt. inc. wire 286.8 g.	17.01.10
Graupner	GM V-MAXX. # 98973		GM LiFe 2S 6.6v. 4000. 35C 1 off tube 3.5mm. Case Black or C/Fibre.	Length: 137.10 mm. Width: 46.31 mm. High: 24.95 mm. Wt. 281.0 g.	17.01.10
Associated Electrics	Reedy # 723		Reedy LiFe 2S 6.6v. 4000 mah. 30C	Length: 136.89 mm. Width: 44.81 mm. High: 23.25 mm. Wt. 268.0 g	17.01.10
Intellect Battery	IP EV Technology # FR2S4000V3		Intellect LiFe 2S 6.6v. 4000 mah. 35C	Length: 137.11 mm. Width: 46.31 mm. High: 24.83 mm. Wt. 280.6 g.	17.01.10
Moore-Speed	Moore-Speed. # MS-B6601		Moore-Speed LiFe 2S 6.6v. 4000 mah. 70C	Length: 138.50 mm. Width: 46.38 mm. High: 24.78 mm. Wt. inc. wire 260.1 g	17.01.10

Paul Worsley, (EFRA Battery Homologation Officer). 05.01.17. (One Page).