



# APPROVED 2S. 'SADDLE' Lithium (LiPo) BATTERY LIST. 2018 v1.

List shows years :- 2012 -- 2018.

Only Batteries detailed below (and any archive lists) are approved for EFRA Sanctioned Events.

## EUROPEAN FEDERATION RADIO CONTROLLED AUTOMOBILES.

### BATTERIES ON THIS HOMOLOGATION LIST HAVE BEEN CERTIFIED FOR COMPLIANCE WITH UN38.3, TESTS T1-T8.

Lithium based (LiPo) batteries detailed below, are approved for various EFRA Electric Classes. Section Rules will detail the type applicable. Availability dates for new EFRA compliant Packs are not known at the date of publishing this list. Manufacturers have confirmed March 2018 latest. EFRA rules do not limit battery power output, but energy capacity has to comply with Airline Requirements, based on Manufacturers data below. Batteries approved from 2011 onwards must comply with the weight range specified. Batteries factory sealed (glue, weld etc.). Battery packs must be able to be disconnected within the Car quickly without the use of tools. Direct soldering is not allowed.

**Manufacturers advise that charge rate be restricted to 1C for optimum lifespan, but should not be more than stated below (for 2017 on). Batteries MUST be charged using a 2S LiPo compatible charger. LiPo 'Sack' must be used when charging or discharging prior to race. It is strictly NOT ALLOWED, to charge 2S LiPo Batteries to give an output voltage exceeding 8.40v.**

| Submitted by:  | Label Details Part #         | Illustration only | Manufacturer Supplied Data.   | EFRA measured Specification,  | Approval Date |
|--|------------------------------|-------------------|---|---|---------------|
| <b>NO 'SADDLE' BATTERIES HAVE BEEN ADDED TO THIS LIST FOR 2018.</b>                                  |                              |                   |   |   |               |
| <b>BATTERIES BELOW THIS LEVEL WERE APPROVED BY EFRA FOR 2017 AND ARE ALLOWED AT ALL 2018 EVENTS.</b> |                              |                   |   |   |               |
| Intellect Battery  | IP # TP2S6000HV2             |                   | Intellect<br>LiPo 2S 2 x 3.8v.<br>2 x 23.0 Wh. 120C<br>Max charge rate: 3C<br>4 mm. Tubes | Sample complies with EFRA dimensions.<br>Weights:-<br>Sample: Pr. 273.9 g.<br>Allowed: 261/283 g. | 05.01.17      |
| Team Corally   | Corally Coral-X # 48374      |                   | Corally<br>LiPo 2S 2 x 3.8v.<br>2 x 22.8 Wh. 100C<br>Max charge rate:1.2C<br>4 mm. Tubes  | Sample complies with EFRA dimensions.<br>Weights:-<br>Sample: Pr. 276.7 g.<br>Allowed: 265/287 g. | 05.01.17      |
| <b>BATTERIES BELOW THIS LEVEL WERE APPROVED BY EFRA FOR 2016 AND ARE ALLOWED AT ALL 2018 EVENTS.</b> |                              |                   |   |   |               |
| LRP  | LRP # 430240                 |                   | LRP<br>LiPo 2S 7.4v.<br>42.9 Wh. 110C<br>Wt. 263/285 g.<br>5 mm. Tubes.                   | Sample complies with EFRA dimensions.<br><br>Sample Wt. 273.9 g.                                  | 14.01.16      |
| LRP  | LRP # 430242                 |                   | LRP<br>LiPo 2S 7.4v.<br>28.9 Wh. 110C<br>Wt. 196/212 g.<br>5 mm. Tubes.                   | Sample complies with EFRA dimensions.<br><br>Sample Wt. 204.5 g.                                  | 14.01.16      |
| LRP  | LRP # 430241                 |                   | LRP<br>LiPo 2S 7.4v.<br>28.9 Wh. 110C<br>Wt. 181/196 g.<br>5 mm. Tubes.                   | Sample complies with EFRA dimensions.<br><br>Sample Wt. 188.6 g.                                  | 14.01.16      |
| LRP  | LRP # 430243                 |                   | LRP<br>LiPo 2S 7.4v.<br>28.9 Wh. 110C<br>Wt. 202/218 g.<br>5 mm. Tubes.                   | Sample complies with EFRA dimensions.<br><br>Sample Wt. 211.3 g.                                  | 14.01.16      |
| Neidhart SA  | Orion # ORI 14085            |                   | Orion<br>LiPo 2S 7.4v.<br>29.6 Wh. 110C<br>Wt. 184/198 g.<br>4 mm. Tubes                  | Sample complies with EFRA dimensions.<br><br>Sample Wt. 193.7 g.                                  | 14.01.16      |
| Nosram   | Nosram X-treme Race # 999533 |                   | Nosram<br>LiPo 2S 7.4v.<br>42.9 Wh. 110C<br>Wt. 263/285 g.<br>5 mm. Tubes.                | Sample complies with EFRA dimensions.<br><br>Sample Wt. 273.4 g.                                  | 14.01.16      |
| Nosram   | Nosram X-treme Race # 999535 |                   | Nosram<br>LiPo 2S 7.4v.<br>28.9 Wh. 110C<br>Wt. 196/212 g.<br>5 mm. Tubes.                | Sample complies with EFRA dimensions.<br><br>Sample Wt. 204.9 g.                                  | 14.01.16      |



|  |  |   |   |   |          |
|--|--|---|---|---|----------|
| Nosram   | Nosram<br>X-treme Race<br># 999534               |     | Nosram<br>LiPo 2S 7.4v.<br>28.9 Wh. 110C<br>Wt. 181/196 g.<br>5 mm. Tubes.        | Sample complies with<br>EFRA dimensions.<br>Sample Wt. 189.9 g. | 14.01.16 |
| Nosram   | Nosram<br>X-treme Race<br># 999536               |    | Nosram<br>LiPo 2S 7.4v.<br>28.9 Wh. 110C<br>Wt. 202/218 g.<br>5 mm. Tubes.        | Sample complies with<br>EFRA dimensions.<br>Sample Wt. 211.1 g. | 14.01.16 |
| RC<br>Concept  | Omega<br>#<br>50C5157200T                        |    | RC Concept<br>LiPo 2S 7.4v.<br>42.2 Wh. 100C<br>Wt. 267/289 g.<br>4 mm. Tubes.    | Sample complies with<br>EFRA dimensions.<br>Sample Wt. 278.4 g. | 14.01.16 |
| Revell GmbH  | TrakPower<br># TKPC0725                          |    | TrakPower<br>LiPo 2S 7.4v.<br>19.0 Wh. X 2 100C<br>Wt. 267/289 g.<br>4 mm. Tubes. | Sample complies with<br>EFRA dimensions.<br>Sample Wt. 275.5 g. | 14.01.16 |
| Shenzhen<br>Grepow   | GensAce<br>#<br>B60C57002S3P<br>H/Case 26        |    | GensAce<br>LiPo 2S 7.4v.<br>42.2 Wh. 60C<br>Wt. 274/296 g.<br>4 mm. Tubes         | Sample complies with<br>EFRA dimensions.<br>Sample Wt. 276.6 g. | 14.01.16 |
| MaxTime  | MTB<br># MTB293                                  |    | Maxtime<br>LiPo 2S 7.4v.<br>42.2 Wh. 100C<br>Wt. 278/302 g.<br>4 mm. Tubes.       | Sample complies with<br>EFRA dimensions.<br>Sample Wt. 293.3 g. | 14.01.16 |
| <b>BATTERIES BELOW THIS LEVEL WERE APPROVED BY EFRA FOR 2015 AND ARE ALLOWED AT ALL 2018 EVENTS.</b> |  |   |   |   |          |
| Intellect<br>Battery   | IP<br># TP2S6000SV1                              |  | Intellect<br>LiPo 2S 7.4v.<br>22.0 (x2) Wh. 100C<br>Wt. 267/289 g.                | Sample complies with<br>EFRA dimensions.<br>Sample Wt. 278.9 g. | 08.01.15 |
| LRP  | LRP<br># 430225                                  |  | LRP<br>LiPo 2S 7.4v.<br>40.7 Wh. 110C<br>Wt. 265/287 g.                           | Sample complies with<br>EFRA dimensions.<br>Sample Wt. 277.5 g. | 08.01.15 |
| LRP  | LRP<br># 430226                                  |  | LRP<br>LiPo 2S 7.4v.<br>27.4 Wh. 110C<br>Wt. 180/196 g.                           | Sample complies with<br>EFRA dimensions.<br>Sample Wt. 190.3 g. | 08.01.15 |
| Modern<br>Creations  | Team<br>Silverback<br>SpiralX<br>#<br>6100902SSP |  | Modern Creations<br>LiPo 2S 7.4v.<br>45.1 Wh. 90C<br>Wt. 254/276 g.               | Sample complies with<br>EFRA dimensions.<br>Sample Wt. 267.0 g. | 08.01.15 |
| Muchmore<br>Racing   | Impact<br>#<br>MLI-IS6000FD2                     |  | Muchmore<br>LiPo 2S 7.4v.<br>44.4 Wh. 90C<br>Wt. 267/289 g.                       | Sample complies with<br>EFRA dimensions.<br>Sample Wt. 278.1 g. | 08.01.15 |
| Nosram   | Nosram<br>X-treme Race<br># 999519               |  | Nosram<br>LiPo 2S 7.4v.<br>40.7 Wh. 110C<br>Wt. 265/287 g.                        | Sample complies with<br>EFRA dimensions.<br>Sample Wt. 274.9 g. | 08.01.15 |
| Nosram   | Nosram<br>X-treme Race<br># 999520               |  | Nosram<br>LiPo 2S 7.4v.<br>27.4 Wh. 110C<br>Wt. 180/196 g.                        | Sample complies with<br>EFRA dimensions.<br>Sample Wt. 189.7 g. | 08.01.15 |



|                                |                                 |   |   |   |          |
|--------------------------------|---------------------------------|---|---|---|----------|
| Process Measurement & Analysis | Optipower<br>#<br>OPR500050BSD  |   | Optipower<br>LiPo 2S 7.4v.<br>37.0 Wh. 50C<br>Wt. 271/293 g.        | Sample complies with<br>EFRA dimensions.<br>Sample Wt. 281.7 g. | 08.01.15 |
| Process Measurement & Analysis | Optipower<br>#<br>OPR500050FLSD |  | Optipower<br>LiPo 2S 7.4v.<br>37.0 Wh. 50C<br>Wt. w/wire 280/304 g. | Sample complies with<br>EFRA dimensions.<br>Sample Wt. 291.8 g. | 08.01.15 |
| Pro Models Corally             | Corally<br># 48279              |  | Pro Models<br>LiPo 2S 7.4v.<br>40.7 Wh. 100C<br>Wt. 283/307 g.      | Sample complies with<br>EFRA dimensions.<br>Sample Wt. 290.3 g. | 08.01.15 |
| ProTek RC                      | ProTek RC<br>#<br>PTK 5112-15   |  | ProTek<br>LiPo 2S 7.4v.<br>38.5 Wh. 100C<br>Wt. 267/289 g.          | Sample complies with<br>EFRA dimensions.<br>Sample Wt. 278.1 g. | 08.01.15 |
| Ruddog Dist.                   | Vampire<br># VR-1029            |  | Vampire<br>LiPo 2S 7.4v.<br>42.2 Wh. 80C<br>Wt. 278/302 g.          | Sample complies with<br>EFRA dimensions.<br>Sample Wt. 291.0 g. | 08.01.15 |

**BATTERIES BELOW THIS LEVEL WERE APPROVED BY EFRA FOR 2014 AND ARE ALLOWED AT ALL 2018 EVENTS.**

|                 |  |   |  |   |          |
|-----------------|--|---|--|---|----------|
| CS-Electronic   | CS<br>Professional<br># C211033          |   | CS<br>LiPo 2S 7.4v.<br>44.4 Wh. 80C<br>Wt. 267/289 g.            | Sample complies with<br>EFRA dimensions.<br>Wt. 279.9 g.        | 05.01.14 |
| Hacker Motor    | Hacker<br>Top Fuel<br># 75700278         |  | Hacker<br>LiPo 2S 7.4v.<br>40.7 Wh. 90C<br>Wt. 277/300 g.        | Sample complies with<br>EFRA dimensions.<br>Wt. 288.2 g.        | 05.01.14 |
| Hobbico RC      | TrakPower<br># TKPC0625                  |  | TrakPower<br>LiPo 2S 7.4v.<br>22 (x2) Wh. 90C<br>Wt. 267/289 g.  | Sample complies with<br>EFRA dimensions.<br>Wt. 278.5 g.        | 05.01.14 |
| VTEC LRP        | VTEC<br># 430213                         |  | LRP<br>LiPo 2S 7.4v.<br>42.9 Wh. 55C<br>Wt. 267/289 g.           | Sample complies with<br>EFRA dimensions.<br>Wt. 279.4 g.        | 05.01.14 |
| Muchmore Racing | Muchmore<br>Impact<br># MLI-<br>IS5000FD |  | Muchmore<br>LiPo 2S 7.4v.<br>37.0 Wh. 50C<br>Wt. 245/265 g.      | Sample complies with<br>EFRA dimensions.<br>Wt. 254.6 g.        | 05.01.14 |
| Neidhart SA     | ORION<br>Carbon Pro<br># ORI 14063       |  | Orion<br>LiPo 2S 7.4v.<br>40.7 Wh. 100C<br>Wt. 276/3300 g.       | Sample complies with<br>EFRA dimensions.<br>Wt. 288.1 g.        | 05.01.14 |
| Neidhart SA     | ORION<br>Carbon Pro<br># ORI 14064       |  | Orion<br>LiPo 2S 7.4v.<br>40.7 Wh. 100C<br>Wt. w/wire 296/320 g. | Sample complies with<br>EFRA dimensions.<br>Wt. w/wire 307.7 g. | 05.01.14 |
| VTEC Nosram     | Nosram<br>X-treme Race<br># 999510       |  | Nosram<br>LiPo 2S 7.4v.<br>42.9 Wh. 55C<br>Wt. 267/289 g.        | Sample complies with<br>EFRA dimensions.<br>Wt. 279.4 g.        | 05.01.14 |

|  |   |   |  |   |          |
|--|---|---|--|---|----------|
| Pro Models<br>BVBA   | Corally<br># 48260                        |     | Corally<br>LiPo 2S 7.4v.<br>42.9 Wh. 90C<br>Wt. 264/286 g.   | Sample complies with<br>EFRA dimensions.<br><br>Wt. 266.3 g.        | 05.01.14 |
| ProTek RC  | ProTek RC<br># PTK LPH<br>2S100 SP        |    | ProTek<br>LiPo 2S 7.4v.<br>40.7 Wh. 100C<br>Wt. 274/296 g.   | Sample complies with<br>EFRA dimensions.<br><br>Wt. 282.1 g.        | 05.01.14 |
| Tianco   | ORCA<br>Infinite<br># OB6090SP            |    | Orca<br>LiPo 2S 7.4v.<br>22.2 (x2) Wh. 90C<br>Wt. 269/291 g.                                       | Sample complies with<br>EFRA dimensions.<br><br>Wt. 283.3 g.        | 05.01.14 |
| Trinity<br>Revtech<br>Epic   | RevTech<br>FormulaX<br># REV2023-5        |    | Revtech<br>LiPo 2S 7.4v.<br>46.25 Wh. 100C<br>Wt. 260/282 g.<br>5mm. Tubes                         | Sample complies with<br>EFRA dimensions.<br><br>Wt. 270.8 g.        | 05.01.14 |
| Xcite RC   | Xcite Energy<br>XXL<br># 56600106         |    | Xcite<br>LiPo 2S 7.4v.<br>44.4 Wh. 80C<br>Wt. 274/296 g.   | Sample complies with<br>EFRA dimensions.<br><br>Wt. 279.2 g.        | 05.01.14 |
| Italtrading  | EZ-Power<br>#<br>EZP6000/1+1              |   | Ital<br>LiPo 2S 7.4v.<br>44.4 Wh. 60C<br>Wt. 267/289 g.  | Sample complies with<br>EFRA dimensions.<br><br>Wt. 277.4 g.        | 05.01.14 |
| nVision  | nVision<br># NVO 1122                     |  | nVision<br>LiPo 2S 7.4v.<br>40.7 Wh. 100C<br>Wt. 274/296 g.  | Sample complies with<br>EFRA dimensions.<br><br>Wt. 284.6 g.        | 05.01.14 |
| nVision  | nVision<br># NVO 1123                     |  | nVision<br>LiPo 2S 7.4v.<br>40.7 Wh. 100C<br>Wt. w/wire 282/306 g.                                 | Sample complies with<br>EFRA dimensions.<br><br>Wt. w/wire 293.2 g. | 05.01.14 |
| RC<br>Industries<br>Int.   | Pro Amps<br>#<br>PA60552SSA               |  | Pro Amps<br>LiPo 2S 7.4v.<br>40.7 Wh. 60C<br>Wt. 252/274 g.  | Sample complies with<br>EFRA dimensions.<br><br>Wt. 262.1 g.        | 05.01.14 |
| Shanghai<br>Dualsky  | Track &<br>Field<br># 33864               |  | Dualsky<br>LiPo 2S 7.4v.<br>39.2 Wh. 70C<br>Wt. 259/281 g.   | Sample complies with<br>EFRA dimensions.<br><br>Wt. 270.4 g.        | 05.01.14 |
| Shenzhen<br>Acepow<br>Electronics  | Gens ace<br>#<br>B50C57002S3<br>Psaddle12 |  | Acepow<br>LiPo 2S 7.4v.<br>42.2 Wh. 50C<br>Wt. 274/296 g.  | Sample complies with<br>EFRA dimensions.<br><br>Wt. 285.3 g.        | 05.01.14 |
| <b>BATTERIES BELOW THIS LEVEL WERE APPROVED BY EFRA FOR 2013 AND ARE ALLOWED AT ALL 2018 EVENTS.</b> |   |   |  |   |          |
| Arrowind<br>Hobby  | Black Magic<br># BM A35<br>4802S          |  | Arrowind Hobby<br>LiPo 2S 7.4v.<br>17.76 Wh. (x2) 35C<br>Wt. 242/262 g<br>Also in Carbon/F finish. | Complies with EFRA.<br>specified dimensions.<br><br>Wt. 254.3 g.    | 02.01.13 |
| Arrowind<br>Hobby  | Black Magic<br># BM A99<br>5002S          |  | Arrowind Hobby<br>LiPo 2S 7.4v.<br>18.5 Wh. (x2) 99C<br>Wt. 248/268 g.<br>Also in Carbon/F finish. | Complies with EFRA.<br>specified dimensions.<br><br>Wt. 258.7 g.    | 02.01.13 |



|   |   |   |   |   |          |
|---|---|---|---|---|----------|
| Associated Electrics  | Reedy<br># 310                              |     | Reedy<br>LiPo 2S 7.4v.<br>21.0 Wh. (x2) 65C<br>Wt. 257/278 g.       | Complies with EFRA.<br>specified dimensions.<br><br>Wt. 267.1 g.                      | 02.01.13 |
| Intellect Battery   | IP<br># TP2S6000V8                          |    | Intellect<br>LiPo 2S 7.4v.<br>22.0 Wh. (x2) 80C<br>Wt. 274/297 g.   | Complies with EFRA.<br>specified dimensions.<br><br>Wt. 286.7 g.                      | 02.01.13 |
| VTEC  | VTEC<br># 430203                            |    | LRP<br>LiPo 2S 7.4v.<br>42.9 Wh. 55C<br>Wt. 269/291 g.              | Complies with EFRA.<br>specified dimensions.<br><br>Wt. 282.8 g.                      | 02.01.13 |
| Modern Creations  | Team Silverback<br>Venus<br># 5600752SSP    |    | Team Silverback<br>LiPo 2S 7.4v.<br>41.44 Wh. 75C<br>Wt. 254/275 g. | Complies with EFRA.<br>specified dimensions.<br><br>Wt. 271.1 g.                      | 02.01.13 |
| VTEC  | Nosram<br>X-treme Race<br># 999503          |    | Nosram<br>LiPo 2S 7.4v.<br>42.9 Wh. 55C<br>Wt. 269/291 g.           | Complies with EFRA.<br>specified dimensions.<br><br>Wt. 282.8 g.                      | 02.01.13 |
| Vampire Racing  | Vampire<br># VR-1024                        |   | Vampire<br>LiPo 2S 7.4v.<br>20.0 Wh. (x2) 70C<br>Wt. 278/301 g.     | Complies with EFRA.<br>specified dimensions.<br>Has chassis locations<br>Wt. 286.8 g. | 02.01.13 |
| Vapex Technology  | VP Racing<br># VP95088                      |  | Vapex<br>LiPo 2S 7.4v.<br>48.0 Wh. 65C<br>Wt. 280/303 g.            | Complies with EFRA.<br>specified dimensions.<br><br>Wt. 292.0 g.                      | 02.01.13 |
| Acorn Innovations   | Acorn Mad<br>Series<br># 1611626            |  | Acorn<br>LiPo 2S 7.4v.<br>20.0 Wh. (x2) 70C<br>Wt. 253/274 g.       | Complies with EFRA.<br>specified dimensions.<br><br>Wt. 264.0 g.                      | 02.01.13 |
| HUECO Handels   | H-Speed<br># HSP-0010                       |  | H-Speed<br>LiPo 2S 7.4v.<br>41.0 Wh. 60C<br>Wt. 288/312 g.          | Complies with EFRA.<br>specified dimensions.<br><br>Wt. 286.2 g.                      | 02.01.13 |
| Shanghai Dualsky  | Track &<br>Field<br># 33864                 |  | Dualsky<br>LiPo 2S 7.4v.<br>39.2 Wh. 70C<br>Wt. 259/281 g.          | Complies with EFRA.<br>specified dimensions.<br><br>Wt. 269.2 g.                      | 02.01.13 |
| Shenzhen Acepow Electronics   | Gens ace<br># B25C51001S3<br>PS12           |  | Acepow<br>LiPo 2S 7.4v.<br>18.9 Wh. (x2) 25C<br>Wt. 280/303 g.      | Complies with EFRA.<br>specified dimensions.<br><br>Wt. 289.8 g.                      | 02.01.13 |
| BATTERIES BELOW THIS LEVEL WERE APPROVED BY EFRA FOR 2012 AND ARE ALLOWED AT ALL 2018 EVENTS. |   |   |   |   |          |
| Advanced Energy   | Thunder<br>Power RC<br># TP5000-<br>2SPR65S |  | Thunder Power<br>LiPo 2S 7.4v.<br>37.0 Wh. 65C<br>Wt. 278/302 g.    | Length: 138.22 mm.<br>Width: 46.46 mm.<br>High: 25.09 mm.<br>Wt. 288.2 g.             | 02.01.12 |
| Hacker Motor  | Hacker<br>Top Fuel<br># 75000278            |  | Hacker<br>LiPo 2S 7.4v.<br>40.7 Wh. 90C<br>Wt. 269/291 g.           | Length: 138.23 mm.<br>Width: 46.64 mm.<br>High: 24.43 mm.<br>Wt. 281.4 g.             | 02.01.12 |

|                                   |                                    |   |   |  |          |
|-----------------------------------|------------------------------------|---|---|--|----------|
| VTEC                              | VTEC<br># 79844                    |   | LRP<br>LiPo 2S 7.4v.<br>41.5 Wh. 55C<br>Wt. 276/298 g.        | Length: 137.46 mm.<br>Width: 46.21 mm.<br>High: 24.77 mm.<br>Wt. 276.3 g.<br>Has chassis location. | 02.01.12 |
| VTEC                              | Nosram<br>X-treme Race<br># 99941  |  | Nosram<br>LiPo 2S 7.4v.<br>41.5 Wh. 55C<br>Wt. 276/298 g.     | Length: 137.44 mm.<br>Width: 46.26 mm.<br>High: 24.73 mm.<br>Wt. 277.6 g.<br>Has chassis location. | 02.01.12 |
| Robitronic<br>Electronic          | Robitronic<br># RO5246             |  | Robitronic<br>LiPo 2S 7.4v.<br>37.0 Wh. 70C<br>Wt. 276/299 g. | Length: 137.76 mm.<br>Width: 45.45 mm.<br>High: 24.88 mm.<br>Wt. 288.6 g.                          | 02.01.12 |
| Shenzhen<br>Acepow<br>Electronics | Gens ace<br># ACE25-<br>4800-0203B |  | Acepow<br>LiPo 2S 7.4v.<br>35.5 Wh. 25C<br>Wt. 269/291 g.     | Length: 138.32 mm.<br>Width: 46.79 mm.<br>High: 24.80 mm.<br>Wt. 280.3 g.                          | 02.01.12 |
| Vapex<br>Technology               | VP Racing<br># VP94449             |  | Vapex<br>LiPo 2S 7.4v.<br>44.5 Wh. 50C<br>Wt. 290/314 g.      | Length: 137.96 mm.<br>Width: 46.07 mm.<br>High: 24.47 mm.<br>Wt. 302.2 g.                          | 02.01.12 |

Paul Worsley, (EFRA Battery Homologation Officer). Updated - 18.01.18. (Six Pages).