

EUROPEAN FEDERATION RADIO CONTROLLED AUTOMOBILES

Samples of Motors included on this list have been checked for compliance to EFRA Rules for:-

Brushless 'Spec.' 10.5T Motors.

Only Motors included on this list, can be used at EFRA Sanctioned events (EC or GP), for:

The Motor Class designated for the event.

Whilst sample Motors submitted have been found to conform with EFRA rules for 'Spec' Brushless Motors, **it is the responsibility of ALL competitors to ensure that the versions they use also comply with all EFRA rules and requirements.**

NOTE: These motors differ from Brushless 'Modified' Motors.

Motor Builder	Type/Range	Illustration only	Notes	Approval Date
Motors below this level must comply with EFRA Rules App.4 :- 4.8 (including 01.03.21 amendment) requiring access to stator to allow measurement and visual appraisal of the laminates. Also 4.9 & 4.16 (including 01.03.21 amendment) which requires the Rotor to be marked with Name or Logo & Part # on shaft.				
Sky RC	ARES Pro V4 Part # SK 400034-01		Sensored system. Stator open. Caps remove. Wind on stator. Adjustable timing 0/+60 deg. Long screws stainless, timing plate screws magnetic, Al. retaining housing, steel shielded magnetic bearings. Rotor with name: Part # SK-715317568 on shaft. No Option rotor submitted.	30.09.25
Reds Racing	VX GEN4 MR Design Part # MTTE 0056H		Must have cut-outs in End-Caps for stator measure. Sensored system. "Y" Wind. Red Al. timing plate. Adjustable timing 0-50. All screws magnetic, Al. sensor housing & retaining plate, magnetic steel shielded bearings. Rotor with name & Part # MSTE 0031 on shaft. Option rotor: MSTE 0041	05.02.25
United Sino Enterprises	ORCA Blitreme3A Part # MO24BT3U105A (EFRA version)		Sensored system. Stator bonded, but has access holes. Wind printed on stator. Adj. timing 5/60. All screws magnetic, steel shielded magnetic bearings. Small dia. steel location pin 5mm long bonded in stator groove. Rotor with ORCA, Part # RT23HS12548 on shaft. Option rotor: RT18M125258 on shaft.	07.10.24
Reds Racing	VX3 Part # MTTE 0035P		Sensored system. Red Al. timing plate. Adjustable timing 0-50. End-Caps remove, cut-outs for measuring stator. All screws magnetic, Al. sensor housing & retaining plate, magnetic steel shielded bearings. Rotor with name & Part # MSTE0041 on shaft. Option rotor: MSTE0031	07.10.24 Rotor change. See also 2020 Approvals
Core RC	Core RC Star Series Fixed timing. Part # CR856		Sensored system. "Y" Wind. Black Al. End-Caps with Core RC. Fixed timing. Stator bonded but wind etched on collector ring. All screws magnetic, steel shielded magnetic bearings. Rotor with Name, Part # CR859 on shaft.	04.07.22
Nosram	XTEC Nosram N22 Part # 920200		Sensored system. "Y" Wind. Black Al. End-Cap with XTEC. Adj. timing 0/60. Wind etched on stator, visible. Body screws non-magnetic, timing screws magnetic, steel shielded magnetic bearings. Rotor with Nosram & Part # 920522 on shaft. Option rotor: 920521.	07.02.22
Ruddog	Ruddog RP542 Part # RP-0446		Sensored system. 4 side screws retain End-Cap. Timing insert with Ruddog. Adjustable timing 0/+60. Wind & RP542 on stator visible. 3mm collector ring. All screws magnetic, Al. sensor housing, magnetic steel shielded bearings. Stator bonded. Rotor with name & Part #- RP-0435	05.04.21
Team Powers	Actinium V4.0 Pt. # TPBLM 105100 ACT-V4		Sensored system. Black Al. one piece Can. 4 full length slots. Team Powers on End-Cap. Wind on stator. Adjustable timing 0-60. Body screws non-magnetic, timing screws magnetic, Al. sensor housing, steel shielded bearings. Rotor with name, Part # TP125G-R2. Option rotor: TP123G-R2	01.03.21

Motors below this level must comply with EFRA Rules App.4 :- 4.8 (prior to 01.03.21 amendment) requiring access to stator to allow measurement and visual appraisal of the laminates. Also 4.9 & 4.16 (prior to 01.03.21 amendment) which requires the Rotor to be marked with Name or Logo & Part #.

Performa	p1 Radical Stock Part # PA9407		Sensored system. "Y" Wind. Stator removes. Adjustable timing 0/+40. Wind in screw slots. All screws magnetic, Al. retaining housing, steel shielded bearings. Rotor with name. Part # PA9355.	07.12.20 05.07.21 Part # updated
Konect	K1 Elite Stock Part # K11901007		Sensored system. "Y" Wind. Stator not bonded and removes for checking. Wind on stator visible. Adjustable timing 0/60. All screws magnetic, Al. retaining housing, magnetic steel shielded bearings. Rotor with name & Part #: K1/12.5C7.2 on flat	06.07.20
Reds Racing	VX3 Part # MTTE 0035 Also: MTTE 0035C See notes		Sensored system. "Y" Wind. Red Al. timing plate. Adjustable timing 0-50. Caps. remove, cut-outs for measuring stator. All screws magnetic, Al. sensor housing & retaining plate, magnetic steel shielded bearings. Rotor with name & Part # MSTE 0030. Motor with Part # ending with C has non-magnetic long body screws.	03.02.20 09.11.20
Absima	CTM V.3 Part # 2130059		Sensored system. Stator removes, access holes. Absima logo End-Cap, wind on sleeve & stator. Adj. timing 0/50. Single collector ring. Body & timing screws non-magnetic, Al. retaining housing, magnetic steel shielded bearings. Rotor with name & Part # CTM STK N42UH.	03.02.20
Corally	Vulcan Stock Part # C-61110		Sensored system. "Y" Wind. Can with Vulcan Stock & wind on stator. Adj. timing 0-60 deg. Stator removes. All screws magnetic, Al. sensor housing. Steel shielded bearings. Rotor with name & Part #: 61130	07.10.19
Surpass	Rocket-RC V5R Part # SUR 51105		Stator removes. Adjustable timing 0/+60 deg. Wind etched on stator. 3mm collector ring. Body screws non-magnetic, timing screws magnetic, Al. retaining housing, steel shielded bearings. Steel body screws supplied with kit, allowed. Rotor with Surpass, Part # C75125 on shaft. Option rotor: C77123 on shaft.	30.09.19
RC Concept	RC Concept CR10 Part # 20410105		Sensored system. "Y" Wind. Stator bonded. Adjustable timing 0/+60. Wind etched on stator. All screws magnetic, Al. retaining plate, steel shielded bearings. Rotor with name. Part # 50126.	03.06.19
RC Streamline	WS Line Part # E19105		Sensored system. "Y" Wind. Sleeve with WS Line & wind on stator. Adj. timing 0-60 deg. Has stator access. Body screws non-magnetic, timing screws magnetic. Al. sensor housing. Steel shielded bearings. Rotor with name & Part #: WSL540S	22.04.19
LRP	XTEC X22 Part # 520200		Sensored system. "Y" Wind. Black Al. End-Bell with XTEC. Adj. timing 0/60. Wind etched on stator. Body screws non-magnetic, timing screws magnetic, steel shielded bearings. Rotor with LRP & Part # 520522, 12.5S on shaft. Option rotor: 520521, 12.3S on shaft. Later motors have two full length slots, and are allowed.	14.01.19 01.07.19
SMC	Lowrider Part # SMCLR42105		Sensored system. "Y" Wind. No centre sleeve, End-Caps remove. Adjustable timing +10/+54 deg. Wind etched on stator. All screws magnetic, Al. retaining housing, steel shielded bearings. Rotor with name & part #: LR712542	24.12.18
Sky RC	ARES Pro. V2.1 Part # SK-400003-57		Sensored system. "Y" Wind. Stator removes. Adjustable timing +5/+55 deg. Wind etched on stator. All screws magnetic, Al. retaining housing, steel shielded bearings. Rotor with name & part #: SK-400003-20	03.12.18

Surpass	Rocket V4S Stock Spec. Part # SUR7105		Sensored system. "Y" Wind. Stator removes. Adjustable timing 0/+60 deg. Wind etched on stator. Body screws non-magnetic, timing screws magnetic, Al. retaining housing, steel shielded bearings. Rotor with Surpass, Part # C75125 on shaft. Option Rotor: C77123 on shaft.	17.09.18 12.11.18
Hobbywing	Xerun V10 G3 Pt # 30401112		Sensored system. "Y" Wind. Black Alu. End-Caps, plastic timing insert. Rotor with one Alu. bal. ring. Adjustable timing +30/+ 60 deg. Stator and wind visible. All screws magnetic, Al. retaining housing, steel shielded bearings. Rotor Part # 30820018. Option rotor 30820406. Later versions can have mounting end-cap chamfer plain aluminium with no black paint.	26.03.18 24.12.18 06.07.20
Motiv	MC2 Part # MOV101052S		Sensored system. "Y" Wind. Alu. timing plate with MOTIV logo. Both End-Caps remove, hysol stator ends. Adjustable sensor plate timing 0/+40 deg. Has stator access. All screws magnetic, full Al. sensor housing, steel shielded bearings. Rotor part # MOV1330	19.02.18
Reds Racing	VX2 Part # MTTE 0021		Sensored system. "Y" Wind. Red Al. timing adjuster. Adjustable timing 0-50. Stator removes & has wind etched. Magnetic screws, Al. sensor housing & retaining plate, steel shielded bearings. Rotor with name & Part # MSTE0017. Option rotor MSTE 0018	15.01.18
Arrowmax	Dash R-Tune Part # DA740105		Sensored system. "Y" Wind. Stator removes. Adjustable timing 0/+60 deg. Wind on stator. All screws magnetic, Al. retaining plate, steel shielded bearings. (Non-magnetic body screws included with kit). Rotor with DASH:- Part # - DA-730003. Shaft RSS125.	01.01.18 19.02.18
NOTE: ALL MOTORS SUBMITTED BEFORE 01.11.17, WERE HOMOLOGATED WITH MAGNETIC SCREWS AND STEEL SHIELDED BEARINGS FITTED. Changing these items invalidates the Motor Part # stated and contravenes App.4 Rule 4.6.				
Trinity	Monster Horsepower Part # TEP 1500 "M"		Sensored system. "Y" Wind. Green end-plate has Trinity & Monster Horsepower etched. Stator sleeve with Trinity, M & Wind etched. Adjustable sensor plate timing 0-60 deg. Has stator access. Wind stamped on lower collector ring. Rotor with name & Part # TEP1112, later versions TEP1119. Either options allowed.	16.10.17 09.04.18
Muchmore	FLETA ZX V2 Part # MR-V2ZX105ER		Sensored system. "Y" Wind. Al. timing plate, adjust. timing 0-50. Stator removes but can be seen through holes. Wind etched on stator. Shaft etched with rotor dia. Rotor with name & part #. Rotor Part #: MR-FZR 21Y. Optional rotor #'s: All MR-FZR :- 18TI, 19Z, 21TIZ, 21Z	24.07.17 31.10.17
PRT Electronic	PRT AIRs 10 Part # A10105S		Sensored system. "Y" Wind. Black Alu. Caps & Sleeve, PRT on End-Plate. Adjustable timing. Caps remove. Wind marked on sleeve. Has stator access. Rotor with name & Part # 125RSHT. Option rotor: 123RSHT	31.05.17
Tesla	Tesla EP Part # TS-194105T-S		Sensored system. "Y" Wind. Blue Alu. Can & End-Caps. Timing insert with Tesla logo etched. Nickel sintered rotor with one Alu. bal. ring. Adjustable timing +20/+ 60 deg. Lams.visible. Rotor Part # TS-194136	15.05.17
PRT Electronic	PRT AIR 10 Part # A10105 (2017 ver.)		Sensored system. "Y" Wind. Black Alu. Caps & Sleeve, PRT on End-Plate. Adjustable timing. Caps remove. Wind marked on sleeve. Has stator access. Rotor with name & Part # 125RSHT. Option rotor: 123RSHT	15.05.17
Hobbywing	Xerun Justock 3650 G2 Pt # 30408004		Sensored system. "Y" Wind. Black Alu. Can & End-Cap with Justock 3650G2. Nickel sintered rotor with one Alu. bal. ring. No timing adjustment. Stator and wind visible. Rotor Part # 30820007 stamped 7-12.5-A.	15.05.17

R1 Brushless Motor Lab.	R1 Part # R1-105B-125-V15 BRCA & EFRA		Sensored system. "Y" Wind. End-Plate with R1 (only) etched. Stator sleeve with wind. Rotor with black balance ring. Adjustable timing 0-60 deg. Has stator access. Collector ring 3mm thick. Motors with epoxy filled windings not approved. Rotor with name & Part #: R1-125-720-002 Option rotors: R1-123-720-001, R1-125-720-001	13.02.17 03.04.17
Orion	Vortex Ultimate Stock LW (2016) # ORI28368		Sensored system. "Y" Wind. Full dia. Black sleeve with removable Alu. End-Plates, all retained with long screws. Adjustable timing 0/+40. Wind etched. Two sensor plug. Rotor has name & part # ORI 41554. Option Rotor: ORI 41553	23.01.17 13.02.17
Maclan	MRR Part # MCL1014		Sensored system. "Y" Wind. Black Can & End-Cap with copper timing plate & logo. Nickel rotor with one red Alu. bal. ring. Adjustable timing +20/+ 60 deg. Stator removes easily. Rotor Part # MCL4075. Optional rotors # MCL4076 & MCL4093.	16.01.17
Tianco	ORCA RT Pt. # OMT105RT		Sensored system. "Y" Wind. Black Can & E/Cap. Stator has access slots. Stator accepts 14.5mm gauge. ORCA RT & wind etched on End-Cap. Adjustable timing +/-50. Rotor with name & Part # ORR325S1. Option rotors:- ORR --- 425S0, 233SL, 238SL, 253SL, 258SL.	16.01.17
Ruddog	Ruddog RP540 Part # RP-0012		Sensored system. "Y" Wind. Silver Alu. Can & End-Caps. Timing insert with Ruddog etched. Nickel rotor with one Alu. bal. ring. Adjustable timing +20/+ 60 deg. Lams.visible with wind visible on stator. Rotor Part # RP-12.5-7.2	05.09.16
Fenix	Fenix DFV2 Pt. # FM00105-2		Sensored system. "Y" Wind. Black Alu. Can & End-Caps. Timing insert with Fenix DFV2 etched. Nickel sintered rotor with one Alu. bal. ring. Adjustable timing +20/+ 60 deg. Laminates.visible. Rotor Part # AP67-B. Option rotor: MF72-B	05.09.16
Corally	Dynospeed Spec. 3.0 Part # C-61100		Sensored system, two ports. "Y" Wind. One end of stator visible but stator removes. Stator has EFRA & wind etched. Wind etched on End-Cap. End-Cap Alum., adjustable timing, no numbers. Rotor with logo, Part # 61130	08.08.16
Tekin	Redline Gen3 Part # TT2708		Sensored system. "Y" Wind. Black Alum. Timing plate 2.5mm above red ring.. Adj. timing 0/60. Machined Alum. Can with wind printed. Stator visible via. slots. Rotor with one brass balance ring Part # 2721. Option rotors: 2719, 2722	16.05.16
Hobbywing	Xerun V10 G2 Pt # 30101106		Sensored system. "Y" Wind. Black Alu. Can & End-Cap, moulded timing insert with logo moulded. Nickel sintered rotor with one Alu. bal. ring. Adjustable timing +20/+ 50 deg. Stator and wind visible. Rotor Part # 30820007 stamped 7-12.5-A Option Rotor # 30820015 stamped 7-12.5-U-B Option End-Cap, timing +30/+60, Part # 30820054	18.01.16 12.12.16 21.11.16
Reedy	Reedy Sonic M3 - SS 1S Part # 285		Sensored system. "Y" Wind. Black Alu. Cap & Sleeve, Alu. timing insert with 'R' logo. Adjustable sensor plate timing 0/+ 50 deg. Caps remove and stator can be removed, wind etched on stator. Nickel sintered rotor with one Alu. balance ring. Rotor Part # 272. Optional Rotors #'s: 273, 286.	28.12.15 15.05.17
Turnigy	Trackstar V2 Pt # 84388		Sensored system. "Y" Wind. Stator slides from sleeve.Sleeve with wind etched. Adjustable sensor plate timing 0-50 deg. Has stator access. Wind etched on stator. Rotor with name, sizes & Part #. Rotor Part # 919000281	23.11.15
For Homologations before 2016 -- See:- Brushless ARCHIVE, All Wind Classes before 2016.				
Paul Worsley. (EFRA Brushless Motor Homologation Officer). email: paul.g.worsley@gmail.com				30.09.25